M28840 Straight Environmental Backshell

NS Series • MIL-DTL-28840 Type Connectors



NSE2 - 009 W


1 2 3

1. **BASIC PART NUMBER**
   - **NSE2** Straight environmental backshell
2. **DASH NO.**
   - See Backshell Dimensions table below
3. **MATERIAL & FINISH**
   - **W** Aluminum, olive drab cadmium
   - **D** Stainless steel, black cadmium plate

Note: See part builder (p. Z-7) for additional kit options.

NSE2 Compatibility

Compatible Brands	Connectors
MIL-DTL-28840	M28840/10, M28840/11, M28840/14, M28840/16



Backshell Dimensions

Dash No.	Shell Size	Military Shell Size	V Thread Class 2B	D Max	T Max	B	L	CC Cable Clearnace	
								Min	Max
001	11	A	.750-20 UNEF	1.028 (26.11)	1.281 (32.5)	.938 (23.8)	3.620 (91.9)	.188 (4.8)	.312 (7.9)
002	11	A	.750-20 UNEF	1.028 (26.11)	1.281 (32.5)	1.125 (28.6)	3.620 (91.9)	.281 (7.1)	.438 (11.1)
003	11	A	.750-20 UNEF	1.028 (26.11)	1.281 (32.5)	1.312 (33.3)	3.620 (91.9)	.344 (8.7)	.562 (14.3)
004	13	B	.875-20 UNEF	1.141 (28.98)	1.281 (32.5)	.938 (23.8)	3.620 (91.9)	.188 (4.8)	.312 (7.9)
005	13	B	.875-20 UNEF	1.141 (28.98)	1.281 (32.5)	1.125 (28.6)	3.620 (91.9)	.281 (7.1)	.438 (11.1)
006	13	B	.875-30 UNEF	1.141 (28.98)	1.281 (32.5)	1.312 (33.3)	3.620 (91.9)	.344 (8.7)	.562 (14.3)
007	13	B	.875-30 UNEF	1.141 (28.98)	1.281 (32.5)	1.312 (33.3)	4.120 (104.6)	.375 (9.5)	.625 (15.9)
008	15	C	1.000-20 UNEF	1.263 (32.08)	1.281 (32.5)	.938 (23.8)	3.620 (91.9)	.188 (4.8)	.312 (7.9)
009	15	C	1.000-20 UNEF	1.263 (32.08)	1.281 (32.5)	1.125 (28.6)	3.620 (91.9)	.281 (7.1)	.438 (11.1)
010	15	C	1.000-20 UNEF	1.263 (32.08)	1.281 (32.5)	1.312 (33.3)	3.620 (91.9)	.344 (8.7)	.562 (14.3)
011	15	C	1.000-20 UNEF	1.263 (32.08)	1.281 (32.5)	1.312 (33.3)	4.120 (104.6)	.375 (9.5)	.625 (15.9)
012	15	C	1.000-20 UNEF	1.263 (32.08)	1.312 (33.3)	1.593 (40.5)	4.120 (104.6)	.438 (11.1)	.750 (19.1)
013	17	D	1.125-18 UNEF	1.387 (35.23)	1.281 (32.5)	1.312 (33.3)	4.120 (104.6)	.375 (9.5)	625 (15.9)
014	17	D	1.125-18 UNEF	1.387 (35.23)	1.312 (33.3)	1.593 (40.5)	4.120 (104.6)	.438 (11.1)	.750 (19.1)
015	17	D	1.125-18 UNEF	1.387 (35.23)	1.406 (35.7)	1.750 (44.5)	4.120 (104.6)	.625 (15.9	.938 (23.8)

Dimensions are in inches (mm).

(Continued on next page)

Backshell Dimensions (Continued from previous page)

Dash No.	Shell Size	Military Shell Size	V Thread Class 2B	D Max	T Max	B	L	CC Cable Clearance	
								Min	Max
016	19	E	1.250-18 UNEF	1.513 (38.43)	1.281 (32.5)	1.312 (33.3)	4.120 (104.6)	375 (9.5)	625 (15.9)
017	19	E	1.250-18 UNEF	1.513 (38.43)	1.406 (35.7)	1.750 (44.5)	4.120 (104.6)	.625 (15.9	.938 (23.8)
018	23	F	1.438-18 UNEF	1.703 (45.51)	1.312 (33.3)	1.593 (40.5)	4.620 (117.3)	.438 (11.1)	750 (19.1)
019	23	F	1.438-18 UNEF	1.703 (45.51)	1.406 (35.7)	1.750 (44.5)	4.620 (117.3)	.625 (15.9	.938 (23.8)
020	23	F	1.438-18 UNEF	1.703 (45.51)	1.593 (40.5)	2.093 (53.2)	4.620 (117.3)	.812 (20.6	1.188 (30.2)
021	25	G	1.562-18 UNEF	1.825 (46.35)	1.406 (35.7)	1.750 (44.5)	4.620 (117.3)	.625 (15.9)	.938 (23.8)
022	25	G	1.562-18 UNEF	1.825 (46.35)	1.593 (40.5	2.093 (53.2)	5.120 (130.0)	.812 (20.6)	1.188 (30.2)
023	25	G	1.562-18 UNEF	1.825 (46.35)	1.593 (40.5	2.093 (53.2)	5.120 (130.0)	.875 (22.2)	1.250 (31.8)
024	25	G	1.562-18 UNEF	1.825 (46.35)	1.625 (41.3)	2.343 (59.5)	5.120 (130.0)	1.000 (25.4)	1.380 (35.1)
025	29	H	1.875-16 UNS	2.143 (54.43)	1.593 (40.5	2.093 (53.2)	5.120 (130.0)	.812 (20.6)	1.188 (30.2)
026	29	H	1.875-16 UNS	2.143 (54.43)	1.625 (41.3)	2.343 (59.5)	5.120 (130.0)	1.000 (25.4)	1.380 (35.1)
027	33	J	2.062-16 UNS	2.329 (59.16)	1.625 (41.3)	2.343 (59.5)	5.120 (130.0)	1.000 (25.4)	1.380 (35.1)
028	33	J	2.062-16 UNS	2.329 (59.16)	1.900 (48.3)	2.750 (69.9)	5.120 (130.0)	1.250 (31.8)	1.625 (41.3)

Dimensions are in inches (mm).

Dimensions are in inches (mm).