

*TF Series • MIL-DTL-5015 Crimp Type Connectors*



**TFAB - 16 N - K2**

- 1 **BASIC PART NUMBER**  
TFAB Boot adapter
  - 2 **SHELL SIZE**  
See Adapter Dimensions table below
  - 3 **MATERIAL & FINISH**  
N Aluminum, electroless nickel  
W Aluminum, olive drab cadmium
  - 4 **OPTIONAL BOOT KIT (OMIT FOR NONE)**  
K2 Includes recommended straight shrink boot in standard material 100, p. X-49  
K4 Includes recommended 90° shrink boot in standard material 100, p. X-50

## TFAB Compatibility

| Compatible Brands  | Connectors                             |
|--------------------|----------------------------------------|
| MIL-DTL-5015 Crimp | MS3400, MS3401, MS3404, MS3406, MS3496 |

**Note:** See part builder (p. X-11) for additional kit options.

## Adapter Dimensions

| Shell Size | CC Cable Clearance | M            | D            | L           | V Thread Class 2B |
|------------|--------------------|--------------|--------------|-------------|-------------------|
| 10         | .355 (9.0)         | .605 (15.4)  | .770 (19.6)  | .832 (21.1) | .625-24 UNEF      |
| 12         | .491 (12.5)        | .774 (19.7)  | .860 (21.8)  | .832 (21.1) | .750-20 UNEF      |
| 14         | .565 (14.4)        | .838 (21.3)  | 1.020 (25.9) | .832 (21.1) | .875-20 UNEF      |
| 16         | .690 (17.5)        | .963 (24.5)  | 1.210 (30.7) | .832 (21.1) | 1.000-20 UNEF     |
| 18         | .769 (19.5)        | 1.042 (26.5) | 1.230 (31.2) | .832 (21.1) | 1.062-18 UNEF     |
| 20         | .894 (22.7)        | 1.217 (30.9) | 1.360 (34.5) | .832 (21.1) | 1.188-18 UNEF     |
| 22         | 1.019 (25.9)       | 1.355 (34.4) | 1.480 (37.6) | .832 (21.1) | 1.313-18 UNEF     |
| 24         | 1.134 (28.8)       | 1.443 (36.7) | 1.730 (43.9) | .832 (21.1) | 1.438-18 UNEF     |
| 28         | 1.369 (34.8)       | 1.709 (43.4) | 1.970 (50.0) | .994 (25.3) | 1.750-18 UNS      |
| 32         | 1.615 (41.0)       | 1.919 (48.7) | 2.220 (56.4) | .994 (25.3) | 2.000-18 UNS      |
| 36         | 1.830 (46.5)       | 2.169 (55.1) | 2.470 (62.7) | .994 (25.3) | 2.250-16 UN       |

Dimensions are in inches (mm).

