

RS06WN12-3PN - L2

- 1 **CONNECTOR PART NUMBER**
Basic RS Series part number
- 2 **BACKSHELL PART NUMBER (ADD TO CONNECTOR)**
L2 Long cable sealing environmental backshell



Note: See part builder (p. V-11) for additional kit options.

RSL2 Compatibility

Compatible Connectors	Compatible Brands
AS95234/1, AS95234/4, AS95234/5, AS95234/6, AS95234/7, AS95234/8, AS95234/9 VG95234 Plugs, VG95234 Receptacles	AS95234 VG95234
GTS00, GTS01, GTS030, GTS06, GTS070, GTC00, GTC01, GTC030, GTC06, GTC070 ACA3100-B, ACA3101-B, ACA3103-B, ACA3106-B 97B-3100, 97B-3101, 97B-3106, 97B-3107, 97B-4100, 97B-4101, 97B-4106, 97B-4107	Amphenol
CA3100, CA3101, CA3106, CB0, CB1, CB6 CIR00, CIR030, CIR06, CIR070	ITT Cannon Veam

Backshell Dimensions

Shell Size	V Thread Class 2B	D	L	B Max
10SL	.625-24UNEF	.787 (20.0)	2.764 (70.2)	.842 (21.4)
14S	.750-20UNEF	.906 (23.0)	2.819 (71.6)	.995 (25.3)
16S	.875-20UNEF	.984 (25.0)	2.890 (73.4)	1.120 (28.5)
16	1.000-20UNEF	.984 (25.0)	3.047 (77.4)	1.120 (28.5)
18	1.125-18UNEF	1.161 (29.5)	3.126 (79.4)	1.216 (30.9)
20	1.250-18UNEF	1.260 (32.0)	3.134 (79.6)	1.403 (35.6)
22	1.375-18UNEF	1.378 (35.0)	3.134 (79.6)	1.403 (35.6)
24	1.500-18UNS	1.516 (38.5)	3.220 (81.8)	1.683 (42.8)
28	1.750-18UNS	1.772 (45.0)	3.417 (86.8)	1.683 (42.8)
32	2.000-18UNS	2.094 (53.2)	3.496 (88.8)	2.050 (52.1)
36	2.250-16UN	2.260 (57.4)	3.559 (90.4)	2.245 (57.0)

Dimensions are in inches (mm).

