

M28876/12 Connector Type Datasheet

NF Series • MIL-DTL-28876 Type Connectors

NF07 W 15-8 S 1 - E2(001) - 02


- 1 **BASIC PART NUMBER**
NF07 Fiber optic jam nut receptacle
- 2 **MATERIAL & FINISH**
W Aluminum, olive drab cadmium
- 3 **SHELL SIZE & INSERT ARRANGEMENT**
See Insert Arrangement Drawings, p. NF-6
- 4 **TERMINUS STYLE**
P Pin
S Socket
- 5 **ALTERNATE KEYING**
1 or 2, 3, 4, 5, 6
- 6 **BACKSHELL KIT**
E2() Straight environmental
(Add dash number for size, see Backshell table)
- 7 **OPTIONAL ACCESSORY KIT (OMIT FOR NONE)**
02 Protective cover



Photo for example only

NF07 Cross Reference & Compatibility

Compatible Brands	Equivalent	Mates
MIL-DTL-28876	M28876/12	MS28876/6, MS28876/7, MS28876/8, MS28876/9
Amphenol	FS3M4, FS3M6, FS3M7	FS3M1, FS3M2, FS3M3



Dimensions

Shell Size	Military Shell Size	D Max	B Max
11	A	.750 (19.1)	.960 (24.4)
13	B	.875 (22.2)	1.085 (27.6)
15	C	1.062 (27.0)	1.255 (31.9)
23	F	1.500 (38.1)	1.763 (44.8)

Dimensions are in inches (mm).

Backshell

Dash No.	Max Cable Clearance by Shell Size			
	11	13	15	23
001	.250 (6.4)	.285 (7.2)	.500 (12.7)	.866 (22.0)
002	.346 (8.8)	.346 (8.8)	.250 (6.4)	1.000 (25.4)
003	—	.453 (11.5)	.375 (9.5)	.600 (15.2)

Rev. 1825