

M85049/3 Environmental Backshell - Style 2

Ry85049 Series • M85049 Type Backshells




Ry85049/3 Compatibility

Compatible Connector Series


MIL-DTL-22992 Classes C, J, & R

Ry85049/3 W 12 A 2

- 1 **BASIC PART NUMBER**
Ry85049/3
 M85049/3 Style 2 type
 Straight environmental backshell
 (Supersedes MS17340/MS90571 Style 2)
- 2 **MATERIAL & FINISH**
W Aluminum, olive drab cadmium
A Aluminum, black anodize
X Aluminum, nickel fluorocarbon polymer
Y Aluminum, pure dense electrodeposited aluminum
Z Aluminum, zinc-nickel
- 3 **DASH NO.**
 See dimensions table below
- 4 **TYPE**
A Plug cap (For use with MS17344 type connectors)
B Receptacle Cap (For use with MS17343, MS17345, & MS17347 type connectors)
- 5 **STYLE**
2 Style 2



Type B With Receptacle Cover



Type A With Plug Cover

(Continued on next page)

Rev. 1825

M85049/3 Environmental Backshell - Style 2

Ry85049 Series • M85049 Type Backshells

Ry85049/3 Dimensions (Continued from previous page)

Dash No.	Shell Size	V Thread Class 2B	M	L	D	H	C Thread Class 2 (A & B)	CC Cable Clearance	
								Min	Max
1	12	0.7500 - 20 UNEF	0.933 (23.7)	4.000 (101.6)	1.094 (27.8)	0.765 (19.4)	0.875-0.1P-0.2L-DS	0.246 (6.2)	0.396 (10.1)
2	14	0.8750 - 20 UNEF	1.057 (26.8)	4.100 (104.1)	1.219 (31.0)	0.765 (19.4)	1.000-0.1P-0.2L-DS	0.321 (8.2)	0.521 (13.2)
3	16	1.0000 - 20 UNEF	1.183 (30.0)	4.400 (111.8)	1.344 (34.1)	0.980 (24.9)	1.125-0.1P-0.2L-DS	0.446 (11.3)	0.646 (16.4)
4	18	1.1250 - 18 UNEF	1.307 (33.2)	4.900 (124.5)	1.469 (37.3)	0.980 (24.9)	1.250-0.1P-0.2L-DS	0.565 (14.4)	0.765 (19.4)
5	20	1.2500 - 18 UNEF	1.433 (36.4)	4.900 (124.5)	1.562 (39.7)	0.980 (24.9)	1.375-0.1P-0.2L-DS	0.690 (17.5)	0.890 (22.6)
6	22	1.3750 - 18 UNEF	1.557 (39.5)	4.900 (124.5)	1.688 (42.9)	0.980 (24.9)	1.500-0.1P-0.2L-DS	0.815 (20.7)	1.015 (25.8)
7	24	1.6250 - 18 UNEF	1.807 (45.9)	5.000 (127.0)	1.938 (49.2)	0.980 (24.9)	1.750-0.1P-0.2L-DS	0.980 (24.9)	1.180 (30.0)
8	28	1.8750 - 16 UN	2.057 (52.2)	5.300 (134.6)	2.219 (56.4)	0.980 (24.9)	2.000-0.1P-0.2L-DS	1.230 (31.2)	1.430 (36.3)
9	28	1.8750 - 16 UN	2.057 (52.2)	5.300 (134.6)	2.219 (56.4)	0.980 (24.9)	2.000-0.1P-0.2L-DS	1.030 (26.2)	1.230 (31.2)
10	32	2.0625 - 16 UNS	2.307 (58.6)	5.600 (142.2)	2.469 (62.7)	0.980 (24.9)	2.250-0.1P-0.2L-DS	1.430 (36.3)	1.670 (42.4)
11	36	2.3125 - 16 UNS	2.557 (64.9)	5.600 (142.2)	2.719 (69.1)	0.980 (24.9)	2.500-0.1P-0.2L-DS	1.660 (42.2)	1.860 (47.2)
12	40	2.6250 - 16 UN	2.870 (72.9)	5.725 (145.4)	2.969 (75.4)	0.980 (24.9)	2.750-0.1P-0.2L-DS	1.860 (47.2)	2.110 (53.6)

Dimensions are in inches (mm).

