

HMMB - 14 - A

- 1
- 2
- 3

BASIC PART NUMBER


HMMB Mounting bracket, aluminum alloy with SST locking nuts

SHELL SIZE

See Bracket Dimensions table below

OPTIONAL FASTENER KIT (OMIT FOR NONE)

- A** Self-sealing SST fillister head screws (4x)
- B** A kit + environmental gasket
- C** A kit + EMI/RFI shielded gasket
- D** A kit + fluorosilicone EMI/RFI gasket



Note: See part builder (p. H-8) for additional kit options.

HMMB Compatibility

Compatible Brands	Receptacles
MIL-DTL-26482 Series 1	MS3110, MS3112
Amphenol	PT00, PT02
Array	PW00, PW02
ITT Cannon	KPT00, KPT02
Souriau	85100, 85102

Bracket Dimensions

Shell Size	W	S	T	H	N	F	Screw Size	Y Thread
8	.880 (22.4)	.594 (15.1)	.308 (7.8)	.570 (14.5)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
10	1.019 (25.9)	.719 (18.3)	.433 (11.0)	.720 (18.3)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
12	1.104 (28.0)	.812 (20.6)	.530 (13.5)	.855 (21.7)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
14	1.198 (30.4)	.906 (23.0)	.624 (15.8)	.984 (25.0)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
16	1.280 (32.5)	.969 (24.6)	.687 (17.4)	1.094 (27.8)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
18	1.406 (35.7)	1.062 (27.0)	.780 (19.8)	1.220 (31.0)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
20	1.535 (39.0)	1.156 (29.4)	.874 (22.2)	1.345 (34.2)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
22	1.665 (42.3)	1.250 (31.8)	.968 (24.6)	1.478 (37.5)	.136 (3.5)	.040 (1.0)	4	4-40 UNJC-3B
24	1.738 (44.1)	1.375 (34.9)	.907 (23.0)	1.483 (37.7)	.153 (3.9)	.040 (1.0)	6	6-32 UNJC-3B

Dimensions are in inches (mm).

