

BMR2 - 009 N

- 1 BASIC PART NUMBER
- 2 DASH NO.
- 3 MATERIAL & FINISH

BMR2 Straight EMI/RFI env. backshell

See Backshell Dimensions table below


N Aluminum, electroless nickel
W Aluminum, olive drab cadmium



Note: See part builder (p. J-11) for additional kit options.

BMR2 Compatibility

Compatible Brands	Connectors
MIL-DTL-26482 Series 2	MS3470, MS3471, MS3472, MS3474, MS3475, MS3476
Aero / Conesys	AE770, AE771, AE772, AE774, AE775, AE776
Amphenol / Matrix	MB10, MB11, MB13, MB14, MB16, MB18
Deutsch	AFD50, AFD51, AFD54, AFD56, AFD57, AFD58
Souriau	8526-0, 8526-5, 8526-6, 8526-7



Backshell Dimensions

Dash No.	Shell Size	V Thread Class 2B	T	D	B	L	CC Cable Clearance	
							Min	Max
005	8	.500-20 UNF	1.544 (39.2)	.617 (15.7)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.250 (6.4)
006	8	.500-20 UNF	1.544 (39.2)	.617 (15.7)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.250 (6.4)
007	8	.500-20 UNF	1.544 (39.2)	.617 (15.7)	1.145 (29.1)	2.875 (73.0)	.250 (6.4)	.437 (11.1)
008	8	.500-20 UNF	1.544 (39.2)	.617 (15.7)	1.145 (29.1)	3.875 (98.4)	.250 (6.4)	.437 (11.1)
009	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.312 (7.9)
010	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
136	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	1.145 (29.1)	2.125 (54.0)	.250 (6.4)	.375 (9.5)
137	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.375 (9.5)
011	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	1.145 (29.1)	2.875 (73.0)	.250 (6.4)	.437 (11.1)
012	10	.625-24 UNEF	1.544 (39.2)	.730 (18.5)	1.145 (29.1)	3.875 (98.4)	.250 (6.4)	.437 (11.1)
114	12	.750-20 UNEF	1.544 (39.2)	.860 (21.8)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.312 (7.9)

Dimensions are in inches (mm).

(Continued on next page)

Rev. 1806

Straight EMI/RFI Env. Backshell

BM Series • MIL-DTL-26482 Series 2 Type Connectors

Backshell Dimensions (Continued from previous page)

Dash No.	Shell Size	V Thread Class 2B	T	D	B	L	CC Cable Clearance	
							Min	Max
115	12	.750-20 UNEF	1.544 (39.2)	.860 (21.8)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
013	12	.750-20 UNEF	1.544 (39.2)	.860 (21.8)	1.145 (29.1)	2.125 (54.0)	.250 (6.4)	.437 (11.1)
014	12	.750-20 UNEF	1.544 (39.2)	.860 (21.8)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
138	12	.750-20 UNEF	1.844 (46.8)	.860 (21.8)	1.332 (33.8)	2.125 (54.0)	.350 (8.9)	.500 (12.7)
139	12	.750-20 UNEF	1.844 (46.8)	.860 (21.8)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.500 (12.7)
111	12	.750-20 UNEF	1.844 (46.8)	.860 (21.8)	1.332 (33.8)	2.125 (54.0)	.350 (8.9)	.500 (12.7)
015	12	.750-20 UNEF	1.844 (46.8)	.860 (21.8)	1.332 (33.8)	2.875 (73.0)	.350 (8.9)	.625 (15.9)
016	12	.750-20 UNEF	1.844 (46.8)	.860 (21.8)	1.332 (33.8)	3.875 (98.4)	.350 (8.9)	.625 (15.9)
150	14	.875-20 UNEF	1.544 (39.2)	.980 (24.9)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.312 (7.9)
151	14	.875-20 UNEF	1.544 (39.2)	.980 (24.9)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
116	14	.875-20 UNEF	1.544 (39.2)	.980 (24.9)	1.145 (29.1)	2.125 (54.0)	.250 (6.4)	.437 (11.1)
117	14	.875-20 UNEF	1.544 (39.2)	.980 (24.9)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
017	14	.875-20 UNEF	1.844 (46.8)	.980 (24.9)	1.332 (33.8)	2.125 (54.0)	.350 (8.9)	.575 (14.6)
018	14	.875-20 UNEF	1.844 (46.8)	.980 (24.9)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.575 (14.6)
019	14	.875-20 UNEF	1.916 (48.7)	.980 (24.9)	1.551 (39.4)	2.875 (73.0)	.500 (12.7)	.750 (19.1)
020	14	.875-20 UNEF	1.916 (48.7)	.980 (24.9)	1.551 (39.4)	3.875 (98.4)	.500 (12.7)	.750 (19.1)
152	16	1.000-20 UNEF	1.544 (39.2)	1.110 (28.2)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.312 (7.9)
153	16	1.000-20 UNEF	1.544 (39.2)	1.110 (28.2)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
112	16	1.000-20 UNEF	1.544 (39.2)	1.110 (28.2)	1.145 (29.1)	2.125 (54.0)	.250 (6.4)	.437 (11.1)
113	16	1.000-20 UNEF	1.544 (39.2)	1.110 (28.2)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
118	16	1.000-20 UNEF	1.844 (46.8)	1.110 (28.2)	1.332 (33.8)	2.125 (54.0)	.350 (8.9)	.625 (15.9)
119	16	1.000-20 UNEF	1.844 (46.8)	1.110 (28.2)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.625 (15.9)
021	16	1.000-20 UNEF	1.916 (48.7)	1.110 (28.2)	1.551 (39.4)	2.125 (54.0)	.500 (12.7)	.700 (17.8)
022	16	1.000-20 UNEF	1.916 (48.7)	1.110 (28.2)	1.551 (39.4)	3.125 (79.4)	.500 (12.7)	.700 (17.8)
023	16	1.000-20 UNEF	2.000 (50.8)	1.110 (28.2)	1.770 (45.0)	2.875 (73.0)	.625 (15.9)	.937 (23.8)
024	16	1.000-20 UNEF	2.000 (50.8)	1.110 (28.2)	1.770 (45.0)	3.875 (98.4)	.625 (15.9)	.937 (23.8)
120	18	1.062-18 UNEF	1.544 (39.2)	1.220 (31.0)	.957 (24.3)	2.125 (54.0)	.125 (3.2)	.312 (7.9)
121	18	1.062-18 UNEF	1.544 (39.2)	1.220 (31.0)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
122	18	1.062-18 UNEF	1.544 (39.2)	1.220 (31.0)	1.145 (29.1)	2.125 (54.0)	.250 (6.4)	.437 (11.1)
123	18	1.062-18 UNEF	1.544 (39.2)	1.220 (31.0)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
025	18	1.062-18 UNEF	1.844 (46.8)	1.220 (31.0)	1.332 (33.8)	2.125 (54.0)	.350 (8.9)	.625 (15.9)
026	18	1.062-18 UNEF	1.844 (46.8)	1.220 (31.0)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.625 (15.9)
027	18	1.062-18 UNEF	1.916 (48.7)	1.220 (31.0)	1.551 (39.4)	2.125 (54.0)	.500 (12.7)	.750 (19.1)
028	18	1.062-18 UNEF	1.916 (48.7)	1.220 (31.0)	1.551 (39.4)	3.125 (79.4)	.500 (12.7)	.750 (19.1)
029	18	1.062-18 UNEF	2.000 (50.8)	1.220 (31.0)	1.770 (45.0)	2.875 (73.0)	.625 (15.9)	.937 (23.8)
030	18	1.062-18 UNEF	2.000 (50.8)	1.220 (31.0)	1.770 (45.0)	3.875 (98.4)	.625 (15.9)	.937 (23.8)
124	20	1.188-18 UNEF	1.544 (39.2)	1.340 (34.0)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
125	20	1.188-18 UNEF	1.544 (39.2)	1.340 (34.0)	1.145 (29.1)	4.125 (104.8)	.250 (6.4)	.437 (11.1)
031	20	1.188-18 UNEF	1.844 (46.8)	1.340 (34.0)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.625 (15.9)
032	20	1.188-18 UNEF	1.844 (46.8)	1.340 (34.0)	1.332 (33.8)	4.125 (104.8)	.350 (8.9)	.625 (15.9)
033	20	1.188-18 UNEF	1.916 (48.7)	1.340 (34.0)	1.551 (39.4)	3.125 (79.4)	.500 (12.7)	.750 (19.1)
034	20	1.188-18 UNEF	1.916 (48.7)	1.340 (34.0)	1.551 (39.4)	4.125 (104.8)	.500 (12.7)	.750 (19.1)
140	20	1.188-18 UNEF	2.000 (50.8)	1.340 (34.0)	1.770 (45.0)	3.125 (79.4)	.625 (15.9)	.904 (23.0)
141	20	1.188-18 UNEF	2.000 (50.8)	1.340 (34.0)	1.770 (45.0)	4.125 (104.8)	.625 (15.9)	.904 (23.0)
035	20	1.188-18 UNEF	2.000 (50.8)	1.340 (34.0)	1.770 (45.0)	3.875 (98.4)	.625 (15.9)	.937 (23.8)
036	20	1.188-18 UNEF	2.000 (50.8)	1.340 (34.0)	1.770 (45.0)	4.875 (123.8)	.625 (15.9)	.937 (23.8)
037	20	1.188-18 UNEF	2.230 (56.6)	1.340 (34.0)	2.113 (53.7)	3.875 (98.4)	.875 (22.2)	1.250 (31.8)
038	20	1.188-18 UNEF	2.230 (56.6)	1.340 (34.0)	2.113 (53.7)	4.875 (123.8)	.875 (22.2)	1.250 (31.8)

Dimensions are in inches (mm).

(Continued on next page)

Rev. 1806

Backshell Dimensions (Continued from previous page)

Dash No.	Shell Size	V Thread Class 2B	T	D	B	L	CC Cable Clearance	
							Min	Max
126	22	1.313-18 UNEF	1.544 (39.2)	1.470 (37.3)	.957 (24.3)	3.125 (79.4)	.125 (3.2)	.312 (7.9)
127	22	1.313-18 UNEF	1.544 (39.2)	1.470 (37.3)	.957 (24.3)	4.125 (104.8)	.125 (3.2)	.312 (7.9)
128	22	1.313-18 UNEF	1.544 (39.2)	1.470 (37.3)	1.145 (29.1)	3.125 (79.4)	.250 (6.4)	.437 (11.1)
129	22	1.313-18 UNEF	1.544 (39.2)	1.470 (37.3)	1.145 (29.1)	4.125 (104.8)	.250 (6.4)	.437 (11.1)
039	22	1.313-18 UNEF	1.844 (46.8)	1.470 (37.3)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.625 (15.9)
040	22	1.313-18 UNEF	1.844 (46.8)	1.470 (37.3)	1.332 (33.8)	4.125 (104.8)	.350 (8.9)	.625 (15.9)
041	22	1.313-18 UNEF	1.916 (48.7)	1.470 (37.3)	1.551 (39.4)	3.125 (79.4)	.500 (12.7)	.750 (19.1)
042	22	1.313-18 UNEF	1.916 (48.7)	1.470 (37.3)	1.551 (39.4)	4.125 (104.8)	.500 (12.7)	.750 (19.1)
043	22	1.313-18 UNEF	2.000 (50.8)	1.470 (37.3)	1.770 (45.0)	3.125 (79.4)	.625 (15.9)	.937 (23.8)
044	22	1.313-18 UNEF	2.000 (50.8)	1.470 (37.3)	1.770 (45.0)	4.125 (104.8)	.625 (15.9)	.937 (23.8)
142	22	1.313-18 UNEF	2.230 (56.6)	1.470 (37.3)	2.113 (53.7)	3.125 (79.4)	.875 (22.2)	1.029 (26.1)
143	22	1.313-18 UNEF	2.230 (56.6)	1.470 (37.3)	2.113 (53.7)	4.125 (104.8)	.875 (22.2)	1.029 (26.1)
045	22	1.313-18 UNEF	2.230 (56.6)	1.470 (37.3)	2.113 (53.7)	3.875 (98.4)	.875 (22.2)	1.250 (31.8)
046	22	1.313-18 UNEF	2.230 (56.6)	1.470 (37.3)	2.113 (53.7)	4.875 (123.8)	.875 (22.2)	1.250 (31.8)
130	24	1.438-18 UNEF	1.844 (46.8)	1.590 (40.4)	1.332 (33.8)	3.125 (79.4)	.350 (8.9)	.625 (15.9)
131	24	1.438-18 UNEF	1.844 (46.8)	1.590 (40.4)	1.332 (33.8)	4.125 (104.8)	.350 (8.9)	.625 (15.9)
047	24	1.438-18 UNEF	1.916 (48.7)	1.590 (40.4)	1.551 (39.4)	3.125 (79.4)	.500 (12.7)	.750 (19.1)
048	24	1.438-18 UNEF	1.916 (48.7)	1.590 (40.4)	1.551 (39.4)	4.125 (104.8)	.500 (12.7)	.750 (19.1)
049	24	1.438-18 UNEF	2.000 (50.8)	1.590 (40.4)	1.770 (45.0)	3.125 (79.4)	.625 (15.9)	.812 (20.6)
050	24	1.438-18 UNEF	2.000 (50.8)	1.590 (40.4)	1.770 (45.0)	4.125 (104.8)	.625 (15.9)	.812 (20.6)
051	24	1.438-18 UNEF	2.000 (50.8)	1.590 (40.4)	1.770 (45.0)	3.125 (79.4)	.625 (15.9)	.937 (23.8)
052	24	1.438-18 UNEF	2.000 (50.8)	1.590 (40.4)	1.770 (45.0)	4.125 (104.8)	.625 (15.9)	.937 (23.8)
144	24	1.438-18 UNEF	2.230 (56.6)	1.590 (40.4)	2.113 (53.7)	3.125 (79.4)	.875 (22.2)	1.144 (29.1)
145	24	1.438-18 UNEF	2.230 (56.6)	1.590 (40.4)	2.113 (53.7)	4.125 (104.8)	.875 (22.2)	1.144 (29.1)
053	24	1.438-18 UNEF	2.230 (56.6)	1.590 (40.4)	2.113 (53.7)	3.875 (98.4)	.875 (22.2)	1.250 (31.8)
054	24	1.438-18 UNEF	2.230 (56.6)	1.590 (40.4)	2.113 (53.7)	4.875 (123.8)	.875 (22.2)	1.250 (31.8)

Dimensions are in inches (mm).

