

Hand Crimpers & Positioners

DS Series • MIL-DTL-38999 Series II Style Connectors



Precision Hand Crimpers

A crimp tool provides reliable crimp termination of contacts for mission-critical applications. A hand crimper is suitable for contacts from size #12 to #22D. For production environments, pneumatic crimpers are also available.

Our tools feature an 8-impession crimp, which ensures maximum tensile strength between wire and contact. Their cycle controlled ratchets are consistent and accurate and do not permit half crimps, ensuring complete and precise crimping every time.

The tool frames have a built-in 8-step selector knob for easy adjustment of crimp depth to accommodate the size of wire being used. Data plates on positioners provide setting information specific to the size of wires and contacts being used.

There are a variety of crimp tools and positioners available to fit the various sized contacts within each connector series. We have paired our most popular models with their required positioner(s) to ensure complete compatibility.

Hand Crimper & Positioner Kits

Part Number	Kit Includes the Following Items	Contacts Sizes	Milnec Series Compatibility	Mil-Spec Series Compatibility
TK101-KIT	TK101A crimp tool with TP104 turret positioner	#20, #16, #12	DL Series, DS, Series, TX Series	MIL-DTL-38999 Series I, II, III
TK101B-KIT	TK101A crimp tool with TP102 turret positioner	#20, #16, #12	BM Series, EV Series, TM Series, HR Series	MIL-DTL-26482 Series I, II MIL-DTL-83723 Series III MIL-DTL-5015 Crimp*
TK201-KIT	TK201 crimp tool with the following positioners: TP209 (for pins), TP207 (for sockets)	#22, #22M, #22D	DL Series, TX Series	MIL-DTL-38999 Series I MIL-DTL-38999 Series III
TK201B-KIT	TK201 crimp tool with the following positioners: TP209 (for pins), TP206 (for sockets)	#22, #22M, #22D	DS Series	MIL-DTL-38999 Series II

* Contacts size #8 and larger require pneumatic crimper. When this is not an option, wires may be soldered directly into contact wire well. For mission critical applications, crimping is preferred termination method.