

## TBD2 - 15 N - K2



- 1
- 2
- 3
- 4

### 1 BASIC PART NUMBER

- TBD2** Straight EMI/RFI banding boot adapter
- TBD3** 45° EMI/RFI banding boot adapter
- TBD4** 90° EMI/RFI banding boot adapter  
(Includes shield termination band TB250, p. R-27)

### 2 SHELL SIZE

See Adapter Dimensions table below

### 3 MATERIAL & FINISH

- N** Aluminum, electroless nickel
- W** Aluminum, olive drab cadmium
- G** Aluminum, electroless nickel (space-grade)
- M** Composite, electroless nickel
- J** Composite, olive drab cadmium

### 4 OPTIONAL BOOT KIT (OMIT FOR NONE)

- K2** Includes recommended straight shrink boot in standard material 100, p. S-18

### TBD2 Compatibility


Compatible Brands	Connectors
<b>MIL-DTL-38999 Series IV</b>	D38999/40, D38999/44, D38999/46, D38999/47, D38999/49
<b>G &amp; H Tech / Cooper</b>	BL00, BL03, BL06, BL07, BLG6
<b>Deutsch</b>	DIV/40, DIV/44, DIV/45, DIV/46, DIV/48

**Note:** Designed for use with straight shrink boot (TBK2, p. S-18).

## Adapter Dimensions

Shell Size	Military Shell Size	CC Cable Clearance	M	D	L	N	K	E	T	V Thread Class 2B
9	A	.250 (6.4)	.437 (11.1)	.858 (21.8)	1.350 (34.3)	1.012 (25.7)	1.161 (29.5)	1.375 (34.9)	1.417 (36.0)	M12 X 1-6H
11	B	.312 (7.9)	.500 (12.7)	.998 (25.4)	1.350 (34.3)	1.031 (26.2)	1.189 (30.2)	1.437 (36.5)	1.480 (37.6)	M15 X 1-6H
13	C	.438 (11.1)	.624 (15.8)	1.161 (29.5)	1.350 (34.3)	1.059 (26.9)	1.209 (30.7)	1.562 (39.7)	1.553 (39.4)	M18 X 1-6H
15	D	.562 (14.3)	.750 (19.1)	1.280 (32.5)	1.350 (34.3)	1.079 (27.4)	1.240 (31.5)	1.687 (42.8)	1.614 (41.0)	M22 X 1-6H
17	E	.625 (15.9)	.812 (20.6)	1.409 (35.8)	1.350 (34.3)	1.110 (28.2)	1.260 (32.0)	1.750 (44.5)	1.678 (42.6)	M25 X 1-6H
19	F	.750 (19.1)	.937 (23.8)	1.520 (38.6)	1.350 (34.3)	1.118 (28.4)	1.272 (32.3)	1.875 (47.6)	1.733 (44.0)	M28 X 1-6H
21	G	.812 (20.6)	1.000 (25.4)	1.642 (41.7)	1.350 (34.3)	1.150 (29.2)	1.299 (33.0)	1.938 (49.2)	1.796 (45.6)	M31 X 1-6H
23	H	.938 (23.8)	1.124 (28.5)	1.772 (45.0)	1.350 (34.3)	1.169 (29.7)	1.331 (33.8)	2.062 (52.4)	1.859 (47.2)	M34 X 1-6H
25	J	1.000 (25.4)	1.187 (30.1)	1.890 (48.0)	1.350 (34.3)	1.201 (30.5)	1.350 (34.3)	2.125 (54.0)	1.919 (48.7)	M37 X 1-6H

Dimensions are in inches (mm).



Rev. 1807